

SILICONE RUBBER - THE FLEXIBLE CHOICE

Article			Mixture	Shore-Hardness	Temperature
Full-type Silicone					
Tubes	inner diameter wall thickness	0,3 to 150 mm 0,3 to 20 mm	technical food medical self-extinguishing electroconducting coloured cadmium free FDA/CFR 21/BGVV XV USP VI additional platinum cured special qualities on request	25 - 80	Qualities from -110°C to +300°C
Cords	diameter	0,5 to 50 mm			
Square profiles	up to a width of up to a height of	200 mm 50 mm			
Profiles	according to draft or sample				

Silicon Sponge			Mixture	Shore-Hardness	Temperature
Tubes	inner diameter wall thickness	1,0 to 70 mm 2,0 to 20 mm	technical coloured self-extinguishing cadmium free food FDA additional platinum cured special qualities on request	5 - 40	Qualities from -80°C bis +300°C
Cords	diameter	0,5 to 50 mm			
Square profiles	up to a width of up to a height of	100 mm 50 mm			
Profiles	according to draft or sample				

Glass silk tubes			Mixture	Shore-Hardness	Temperature
silicone coated	inner diameter	from 0,5 to ca. 50 mm	coloured	impregnated, to 8 KV	up to +250°C
polyurethan-lackiert	inner diameter	from 0,5 to 10 mm	coloured	impregnated, to 4 KV	up to +155°C